

# SILENTFIBER™ POLY BOARD CLEANING INSTRUCTIONS

## BEFORE CLEANING:

Polyboard is a porous material that will allow fluids and debris to penetrate the surface. The nature of cleaning polyboard must be approached much like carpet. It is important to lift as much of the debris and stain as possible, as 'rubbing' the stain will only help it penetrate the board further.

## DUST AND DEBRIS REMOVAL:

It is recommended that loose dust and debris be lightly vacuumed with a clean nozzle. Compressed air is not recommended as the air may force debris further into the board, and will also spread dust through the air to other areas.

## STAIN REMOVAL:

If the stain is in liquid form, a light absorptive towel is recommended to lightly blot the stain to soak it up. Once all 'excess' stain is removed from the polyboard, continue to remove as much of the remaining stain as possible with a clean vacuum nozzle.


If the stain has dried, it is recommended to 'pick off' the excess from the board. Once all excess is removed, a portable carpet cleaner should be used to dissolve the stain and vacuum it up. It is important that distilled water be used. Polyboard will not retain water, but hard water or water with minerals may leave a stain.

## DISINFECT:

Sound Acoustic Solutions recommends guidance through the CDC for an appropriate mixture or formula to disinfect whatever stain you may encounter. Disinfectant and over the counter antimicrobial fabric spray should take care of most issues.

1215 Valley Belt Rd. | Brooklyn Heights, OH 44131  
[info@soundacousticsolutions.com](mailto:info@soundacousticsolutions.com)  
[www.SoundAcousticSolutions.com](http://www.SoundAcousticSolutions.com)  
+1 (877) 399-9697

Scan QR code for product data:



**sound**  
acoustic  
SOLUTIONS